



# 1 SAT IF distribution equipment Power supplies & accessories

## Power supplies

- switch-mode technology
- short circuit and overload protected
- DIN rail mounting (HDR-60-12)



Technical specifications		
T Y P E	HDR-60-12	SGA25E12-W
Ordering number	00631	00633
DC output	+12 V 4.5 A max.	+12 V 2 A max.
Mains voltage	100 V ÷ 240 V ~ 50/60 Hz	
Operating temperature range	-20° ÷ +50° C	-20° ÷ +40° C
Dimensions/Weight (packed)	52.5x90x54.5 mm/0.3 kg	75.5x32x47.5 mm/0.16 kg

## Accessories

- Fmale - Fmale quick coaxial bridge 699.026: for modules with width 36 mm  
Ordering number 21876
- Fmale - Fmale quick coaxial bridge 780.026: for modules with width 48.5 mm  
Ordering number 21881



- 19" system mountable rack  
Ordering number 01957



- DC distribution cable 699.20 for 4 modules with width 36 mm  
Ordering number 21875
- DC distribution cable 780.20 for 4 modules with width 48.5 mm  
Ordering number 21882



- Rail for wall mounting, 1 meter, 699.027  
Ordering number 21877



- DC distribution cable 908.20 for 12 modules  
Ordering number 21883

