

UV-UAC-T115-F28-W

Cámara Analógica 5 Megapíxel
Gama Easy
1/2.7" Progressive Scan CMOS
Lente 2.8 mm / COLORHUNTER
IR LEDs Alcance 20 m
IP67



Uniview
Cámara Turret Analógica
1/2.7" Progressive Scan CMOS
5 Megapíxel (2880x1620)
Lente 2.8 mm
0.02 Lux
IR Alcance 20 m
Luz Blanca
Impermeable IP67
IR CUT
TVI/AHD/CVI/CVBS
COLORHUNTER

Especificaciones

Gama	Uniview
Sensor de imagen	1/2.7" Progressive Scan CMOS
Resolución máxima	5MP
Tasa Main Stream	5MP@25fps: 2880x1620; 5MP@20fps: 2592x1944; 5MP@12.5fps: 2592x1944
Tasa Extra Stream	4MP: 2560x1440; 2MP: 1920x1080
Lente	2.8 mm
Iluminación mínima	0.02 Lux (Color)
Alcance Infrarrojos	20 m
Luz Blanca	Si
Mejoras de imagen	BLC, HLC, DWDR, DAY/NIGHT MODE, 2D. DWDR. SMART IR
Día / Noche	Filtro mecánico ICR
Alimentación	DC 12 V / 2.04 W
Salida de vídeo	TVI: 5MP@20fps, 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps AHD: 5MP@20fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVBS: PAL, NTSC
Interface	5.5 mm
Temp. funcionamiento	-30° C ~ 60° C
Grado de protección	Impermeable IP67
Dimensiones	7118mm*96mm
Peso	205 g