

Amplificadores monocanal / Amplificadores monocanal / Amplificateurs monocanal / Single channel amplifiers / Amplificatore di singolo canale / Einkanal Verstärker / Wzmacnianie pojedynczego kanału / Канальный усилитель T.12

Características técnicas / Características técnicas / Caracteristiques techniques / Technical specifications / Caratteristiche Tecniche / Technische Daten / Specyfikacja techniczna / Технические характеристики

Ref.		508112	508212	508312	508712	509912	508812	508912	508612	509812	508012	
	f_w	MHz	47-100	87.5-108	174-230	104-174	195-232	230-300	302-470	470 - 862	950-2150	
	BW	MHz	7	-	7	7	37	7	8	8 \rightarrow 56	8	950-2150
	G		50	35	45	58	45	58	58	50	55	35 \rightarrow 50
	EQ	dB	35	35	35	35	35	35	35	30	30	20
	V_{out}	A	123*	114*	123*	125*	-	124*	125*	125 \rightarrow 111*	125*	124**
		D	-	-	-	-	114***	-	-	118 \rightarrow 102*	118*	
	I	mA	100								400	
	V	Vdc	24								13/17	
		KHz	-								0/22	
	I_c	mA	70				95				130	
	P	dB	≤ 1	<3	<3	<1	<3	<1	<1	<3	<2	-
	R_{n+1}		-	-	-	-	-	-	-	>3	>18	-
	R_{n+2}	dB	>40	-	>30	>30	>20	>25	>30	>15	>50	-
	R_{n+3}		-	-	-	-	-	-	-	>20	-	-
Noise Figure / Коэффициент шума	NF	dB	<9								<11	<12.5
		mm	107 x 35 x 198									
		grs	600									
IP			IP 20									

(*): EN 50083-5; (**): DIN VDE0855/12; (***) $d_i = 50$ dB (2 ch. 4 MHz)



